

Estimation of Critical Flow Velocity for Collapse of Gas Test Loop Booster Fuel Assembly

ICONE 14

Donna Post Guillen
Mark J. Russell

July 2006

The INL is a
U.S. Department of Energy
National Laboratory
operated by
Battelle Energy Alliance



This is a preprint of a paper intended for publication in a journal or proceedings. Since changes may be made before publication, this preprint should not be cited or reproduced without permission of the author. This document was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, or any of their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for any third party's use, or the results of such use, of any information, apparatus, product or process disclosed in this report, or represents that its use by such third party would not infringe privately owned rights. The views expressed in this paper are not necessarily those of the United States Government or the sponsoring agency.

ICONE14–89130

ESTIMATION OF CRITICAL FLOW VELOCITY FOR COLLAPSE OF GAS TEST LOOP BOOSTER FUEL ASSEMBLY

Donna Post Guillen and Mark J. Russell

Idaho National Laboratory
Idaho Falls, Idaho 83415

ABSTRACT

This paper presents calculations performed to determine the critical flow velocity for plate collapse due to static instability for the Gas Test Loop booster fuel assembly. Long, slender plates arranged in a parallel configuration can experience static divergence and collapse at sufficiently high coolant flow rates. Such collapse was exhibited by the Oak Ridge High Flux Reactor in the 1940s and the Engineering Test Reactor at the Idaho National Laboratory in the 1950s. Theoretical formulas outlined by Miller, based upon wide-beam theory and Bernoulli's equation, were used for the analysis. Calculations based upon Miller's theory show that the actual coolant flow velocity is only 6% of the predicted critical flow velocity. Since there is a considerable margin between the theoretically predicted plate collapse velocity and the design velocity, the phenomena of plate collapse due to static instability is unlikely.

INTRODUCTION

A Gas Test Loop (GTL) system is currently being designed to provide a high intensity fast-flux irradiation environment for testing fuels and materials for advanced concept nuclear reactors. To assess the performance of candidate reactor fuels, these fuels must be irradiated under actual fast reactor flux conditions and operating environments, preferably in an existing irradiation facility [1]. The GTL system is being designed for operation in the northwest test lobe of the Advanced Test Reactor (ATR) at the Idaho National Laboratory. The Technical and Functional Requirements (T&FRs) for the GTL stipulate a minimum neutron flux intensity (10^{15} n/cm²·s) and fast to thermal neutron ratio (>15) for the test environment [2]. Incorporation

of booster fuel within the test lobe is necessary to achieve these neutron flux requirements.

The current design of the booster fuel assembly (BFA) for the GTL calls for 3 concentric rings of uranium silicide fuel plates clad with 6061 aluminum arranged in four quadrants (shown in Figure 1). The fuel plates are 0.1 inches (0.254 cm) thick, 4 foot (1.22 m) long, and separated by 0.078 inch (0.198 cm) water coolant channels.

PLATE COLLAPSE PHENOMENON

Long parallel plate fuel assemblies can experience static divergence and collapse at sufficiently high coolant flow rates. Such phenomenon has occurred at the Oak Ridge High Flux Reactor [3] in the 1940s and the Engineering Test Reactor at the Idaho National Laboratory [4] in the 1950s. When the coolant flow reaches a critical static divergent velocity, U_d , parallel plate fuel assemblies will buckle and collapse onto each other as a result of a flow-induced asymmetric pressure distribution in adjacent flow channels [5]. Analysis was performed herein to determine whether the GTL booster fuel assembly (BFA) is likely to collapse at the current design flow rate due to a flow-induced static-instability type of failure.

Fuel plate collapse stems from plate deformation, which can be caused by unbalanced channel pressures created by turbulence, pressure fluctuations produced by the primary coolant pumps, unequal flow in the channels due to assembly tolerances, etc. Pressure forces act to deflect the fuel plates. Excessive lateral deformation of long parallel plates subject to axial flow can occur due to unbalanced channel pressures when the pressure difference across the plates is too large for the plate to resist [6]. As the plates deform and the flow

channel narrows, the flow velocity increases. By Bernoulli's equation, the pressure correspondingly decreases, and this causes an increase of the pressure differential across the plate with a corresponding increase in deformation. This deformation is resisted by elastic restoring forces developed in

Fig. 1. Current booster fuel assembly configuration and dimensions.

The moment of inertia of the beam cross section per unit width of beam is given by

$$I := \frac{\frac{w \cdot a^3}{12}}{w} \quad (8)$$

and

$$I = 8.333 \times 10^{-5} \text{ in}^3 \quad (9)$$

The minimum radius of curvature of fuel plate is used to minimize the critical velocity ratio

$$R := \min\left(\frac{R_o + R_i}{2}\right) \quad (10)$$

and

$$R = 2.141 \text{ in} \quad (11)$$

Half the curved plate arc between supports, α , is

$$\alpha := \frac{\pi}{4} \quad (12)$$

From Miller [3]

$$C(\alpha) := \frac{-2}{3} + \sin(2\alpha) \cdot \left(\frac{3}{4} \cdot \cot(\alpha) - \alpha\right) - \frac{4}{3} \cdot \cos(2\alpha) \dots \\ + \alpha \cdot \cot(\alpha) \cdot \left(1 - \frac{\cos(2\alpha)}{2}\right) \quad (13)$$

and

$$C(\alpha) = 0.083 \quad (14)$$

Miller [3] also defines the following variables

$$f_1(\alpha) := \frac{1}{2 \cdot \sin(\alpha)^2} \cdot \left(\frac{\alpha}{2} + \frac{\sin(2\alpha)}{4}\right) \quad (15)$$

$$f_3(\alpha) := \frac{1}{2 \cdot \sin(\alpha)^2} \cdot \left(\alpha - \frac{3}{4} \cdot \sin(2\alpha) + \frac{\alpha \cdot \cos(2\alpha)}{2}\right) \quad (16)$$

$$\beta_2 := \frac{A \cdot R^2}{I} \cdot f_3(\alpha) + f_1(\alpha) \quad (17)$$

The ratio of pinned edge curved plate to pinned edge flat plate critical velocity is

$$V_{rh} := \left(\frac{8 \cdot \beta_2 \cdot \sin(\alpha)^5}{15 \cdot C(\alpha)}\right)^{\frac{1}{2}} \quad (18)$$

and

$$V_{rh} = 14.9 \quad (19)$$

Now, the pinned edge velocity to which the above ratio applies is calculated. The gravitational acceleration constant is

$$g = 386.089 \frac{\text{in}}{\text{sec}^2} \quad (20)$$

Young's Modulus for the fuel plate using room temperature data for aluminum (1000 series) is [8]

$$E = 10 \cdot 10^6 \cdot \text{psi} \quad (21)$$

Poisson's ratio of the fuel plate is taken to be that of aluminum [9]

$$\nu = 0.33 \quad (22)$$

The fuel element channel widths, h_{el} , are

$$h_{el1} := R_{i1} - R_{o_{i+1}} \quad (23)$$

which results in an initial flow channel thickness, h , of

$$h := \min(h_{el}) \quad (24)$$

and

$$h = 0.078 \text{ in} \quad (25)$$

The average density of the water coolant is

$$\rho := 62.24 \frac{\text{lb}_f}{\text{ft}^3} \quad (26)$$

The dimension of end plate is

$$ep = 0.533 \text{ in} \quad (27)$$

The width of the flat plate is taken as arc length of curved plate minus end plate

$$b := 2 \cdot \alpha \cdot R - ep \quad (28)$$

and

$$b = 2.83 \text{ in} \quad (29)$$

The critical velocity of pinned edge flat plate is

$$V_s := \left[\frac{5 \cdot g \cdot E \cdot a^3 \cdot h}{2 \cdot \rho \cdot b^4 \cdot (1 - \nu^2)} \right]^{\frac{1}{2}} \quad (30)$$

which yields

$$V_s = 50.39 \frac{\text{ft}}{\text{sec}} \quad (31)$$

The critical static divergent velocity for the curved plate GTL booster fuel assembly is the product

$$U_d := V_s \cdot V_{rh} \quad (32)$$

which yields

$$U_d = 749.2 \frac{\text{ft}}{\text{sec}} \quad (33)$$

The total cross-sectional flow area of the four fuel channels is

$$XA := 2.50379 \cdot 10^{-3} \cdot \text{m}^2 \quad (34)$$

The total coolant flow rate necessary to produce plate collapse is the product of the cross-sectional flow area and the critical static divergent velocity

$$Q := U_d \cdot XA \quad (35)$$

which results is a critical flow rate of

$$Q = 9.062 \times 10^3 \text{ gpm} \quad (36)$$

DISCUSSION OF RESULTS

The theoretical collapse velocity for flat plates with simply supported edges was calculated first. Then, the ratio of the critical velocity of hinged curved plates to that of hinged flat plates was calculated. The critical velocity for the hinged curved plate assembly was calculated by multiplying the predicted collapse velocity for hinged flat plate assemblies by this critical velocity ratio. Due to the higher stiffness of the curved plate assembly, the critical velocity is approximately 15 times higher than that for a long flat plate assembly with identical dimensions.

The predicted plate collapse velocity, U_d , for the GTL booster fuel assembly is 228 m/s (749 ft/s). This would occur at a total coolant flow rate around 9100 gpm. Preliminary calculations performed using RELAP5-3D using a fuel plate surface roughness of 1.31 microns, predict an average coolant flow velocity of approximately 10.5 m/s (34.4 ft/s) with the snubber tube included and 13.4 m/s (44.0 ft/s) without the snubber tube. The total coolant design flow rate without the snubber tube is 533 gpm [10]. The snubber tube is part of the

original ATR design intended to hydraulically slow the control rod as it reaches the bottom of its travel path.

Miller states “in some fuel-plate assemblies collapse has occurred at velocities on the order of one-half of that predicted by the formulas here” [3]. In the absence of a considerable margin between the theoretically predicted plate collapse velocity and the design velocity, a test program would be warranted. However, since the coolant design flow velocity is only 6% of the predicted critical flow velocity based upon Miller’s theory, the phenomena of plate collapse due to static instability is unlikely. However, this does not rule out the possibility of plate collapse caused by other mechanisms, such as thermoelastic instability, creep, radiation-induced fuel meat distortion, etc., which may need to be investigated.

ACKNOWLEDGMENTS

This manuscript has been authored by Battelle Energy Alliance, LLC under Contract No. DE-AC07-05ID14517 with the U.S. Department of Energy. References herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the U.S. Government, any agency thereof, or any company affiliated with Idaho National Laboratory.

REFERENCES

1. “Justification of Mission Need for the Gas Test Loop,” Idaho National Laboratory, *INEEL/EXT-04-02018*, June 2004.
2. Longhurst, G.R., and Khericha, S.T., “Gas Test Loop Technical and Functional Requirements,” Draft, Rev. A, Idaho National Laboratory, *INEEL/EXT-04-02273*, July 2005.
3. Miller, D.R., “Critical Flow Velocities for Collapse of Reactor Parallel-Plate Fuel Assemblies,” *Journal of Engineering for Power*, April 1960, p. 83-95.
4. Stromquist, W.K., and Sisman, O., “High Flux Reactor Fuel Assemblies – Vibration and Water Flow,” Report No. ORNL-50, June 15, 1948
5. Doan, R.L., “The Engineering Test Reactor – A Status Report,” *Nucleonics*, Vol. 16, No. 1, 1958, p. 102-105.
6. Ho, M., Hong, G., and Mack, A.N.F., “Experimental Investigation of Flow-Induced Vibration in a Parallel Plate Reactor Fuel Assembly,” *15th Australasian Fluid Mechanics Conference*, Sydney, Australia, December 13-17, 2004.
7. Paidoussis, M.P., *Fluid-Structure Interactions: Slender Structures and Axial Flow*, Vol. 2, Elsevier Academic Press, New York, 2004, p. 1181-1186.
8. 2004 ASME Boiler & Pressure Vessel Code, Section II, “Materials,” Part D, “Properties (Customary),” Subpart 2, “Physical Property Tables,” Table TM-2, “Moduli of Elasticity E of Aluminum and Aluminum Alloys for Given Temperatures,” *American Society of Mechanical Engineers*, 2004 Edition, 2005 Addenda.
9. *Mark's Standard Handbook for Mechanical Engineers*, 8th Edition, McGraw Hill, New York, 1978, Table 3, p 5-5.

10. Guillen, D.P., and Yoder, T.S., "Specification of Surface Roughness for Hydraulic Flow Test Plates," *Proceedings of the 5th International Surface Engineering Congress*, Seattle, WA, May 15-17, 2006.